


Richter Magnetic Drive Process Pumps

ISO/DIN, ASME/ANSI

Corrosive, solids-laden and high-purity fluids



Temperatures to
150 °C (300 °F)

Lining PFA/PTFE

Pure SSiC sleeve
bearing system

SAFEGLIDE® PLUS
dry-run optimization



RICHTER
Process Pumps & Valves



V&A

IPEX
FLUID & METERING

Lined magnetic drive process pumps

Fields of application

Corrosive, environmentally critical and high-purity fluids in the chemical, pharmaceutical, petrochemical, semiconductor, pulp, metal, food processing and waste disposal/recycling industries.

The RMI (ISO/DIN) and RMA (ASME/ANSI) series were developed

- for use with media where stainless steel and conventional polymers such as PE, PP etc. do not have sufficient corrosion resistance
- as an alternative to
 - pumps made of expensive long-lead-time metals (Alloy C, titanium, nickel, etc.)
 - mechanical seal pumps
 - full polymer pumps
 - metal pumps with double mechanical seals and liquid sealing or quenching systems
 - and stainless steel magnetic drive pumps.

Design

Sealless, fluoropolymer-lined, mag-drive centrifugal pumps. Dimensions and delivery data to ISO/EN 22858/ISO 2858 and ASME/ANSI B73.3.

Close-coupled and frame-mounted designs.

No dynamic seal. Eddy-current-free.

- Frame-mounted

ISO/DIN	RMI/F...
ASME/ANSI	RMA/F...
- Close-coupled

ISO/DIN	RMI-B/F...
ASME/ANSI	RMA-B/F...
- Lining: Perfluoroalkoxy (PFA)
- ATEX and Clean Air Act (TA Luft) conformity

Operating range

	50 Hz operation	60 Hz operation
RMI	0.1-130 m³/h* 0.4-570 USgpm* up to 70 m (230 ft) LC*	0.1-150 m³/h* 0.4-660 USgpm* up to 100 m (330 ft) LC*
RMA	0.1-250 m³/h* 0.4-1100 USgpm* up to 110 m (360 ft) LC*	0.1-300 m³/h* 0.4-1320 USgpm* up to 155 m (500 ft) LC*

- Temp. -30 °C to 150 °C* (-20 °F to 300 °F)*; up to 20 bar (290 psi)
- Capability of handling solids-laden fluids depending on shape, hardness and size of the solids. Consult factory.

* For higher temperatures and flow rates, see Richter series MNK (ISO/DIN) and MNKA (ASME/ANSI).

Features and benefits

The handling of highly corrosive, high-purity or environmentally critical fluids calls for truly reliable and safe pumps – without compromises on quality, material and efficiency.

The RMI and RMA series excel through

- ① **Pure PFA lining without fillers – perfect lining quality with even lining thickness**
 - **Highest chemical resistance**, well above ETFE (e.g. Tefzel®) and PVDF
 - Temperatures up to 150 °C (300 °F)
 - **Full FDA conforming materials**
 - Neutral to pure and high-purity fluids in pharmaceutical, fine chemical and semiconductor applications
 - Superb permeation resistance
 - Wall thickness of at least **3 to 5 mm (0.1 to 0.2 inch)**.
 - **Vacuum-proof anchored housing lining:**
Richter exclusively uses the “**TM transfer moulding process**” (not the so-called roto-moulding process). Indexing drillings on casting outside guarantee uniform lining thickness: important for high permeation resistance.
- ② **SAFEGLIDE® PLUS optional**
 - **Optimised dry-run capability.** As a result, dry-running is possible for 30-60 minutes. The proprietary surface impregnation is extremely wear and chemical-resistant. Supplied with more than 20,000 Richter pumps.
- ③ **Capable of handling fluids containing solids**
 - **Solids restriction rings in the housing and rotor** prevent critical solid particles from entering the can area.
- ④ **High efficiency and low NPSHr impeller design**
 - Smooth running even under critical load conditions
 - Axially thrust-optimised rotating unit
 - The **shaft made of SSiC** is optimally supported between the can and in the spider without any shaft deflection.
 - The wide spacing between the SSiC sleeve bearings provides even distribution of the radial forces.
- ⑤ **Minimum life cycle costs and ease of maintenance**
 - High efficiency design, no energy-wasting eddy currents
 - High corrosion resistance covers a large range of chemicals.
 - Virtually maintenance-free
 - Double “back pull-out” design for easy maintenance without removal from piping
 - Few components only: a service-friendly pump

⑥ **Sturdy design for dimensional stability even at high temperatures**


- Full-surface ductile cast iron EN-JS 1049/ASTM A395 allows for higher pump pressure and temperature rating than an all plastic pump
- Impeller magnet assembly provides stable metal core
- Highest grade SSiC silicon carbide sleeve bearing system for resistance of chemical abrasion and corrosion

⑦ **Non-metallic double can system**

- Wetted: thick-walled pure PTFE
- Pressure-bearing: carbon-fibre, with high safety reserves
- No eddy currents: no heating of fluid, no energy waste

⑧ **High-performance NdFeB (neodymium iron boron) and SmCo (samarium cobalt) permanent magnets**

- Consistent magnetic energy density even at high operating temperatures
- Patented magnet attachment underneath the PFA lining



⑨ **Bump ring prevents containment breach**

- In the event of ball bearing failure, a bump ring in the lantern prevents the outer magnet from tumbling and contacting with the containment can

⑩ **High-quality external corrosion protection**

- Thick outside epoxy coating
- SS fasteners, other grades optional

⑪ **Impeller/magnet assembly in two pieces**

- In case of torque adjustment or wear the wetted rotor components can be replaced individually. This enhances cost-efficiency.
- Completely homogenous PFA lining, no seams



Close-coupled pumps RMI-B, RMA-B

All sizes are available both in compact close-coupled design for a flange motor and in frame-mounted design.

Quality and reliability count when difficult fluids are to be handled

SAFEGLIDE® PLUS dry-run optimised silicon carbide (SSiC) bearing system

SSiC and SAFEGLIDE® PLUS are extremely corrosion and abrasion resistant. The SSiC radial sleeve bearings are positively locked in the impeller/magnet assembly and rotate on the SSiC shaft. The SSiC impeller thrust ring absorbs possible axial thrust.

SAFEGLIDE® PLUS is a most valuable option and offers unique dry-run properties.

It protects against dry-run damage for a reasonable period should lubricating fluid be missing!

Carbon graphite sleeve bearings are not offered due to fast wearing.



Shaft and sleeve bearing made of SSiC




Double can system

Pure PFA and PTFE fluoropolymer lining, no fillers

Any filler – be it e.g. graphite, glass powder or carbon fibre – has a negative impact on the overall chemical and permeation resistance of fluoropolymers against corrosive chemicals and on the inertness versus high-purity and valuable fluids. Fillers are usually compounded in for dimensional stability of the liner or component at higher temperatures or pressures.

The metal core used in Richter pumps is the more reliable solution and also provides more flexibility as pumps lined with pure PFA can also operate as multi-purpose pumps with higher temperature ranges.

Comparison of temperature rise over time: Standard SSiC vs SAFEGLIDE® PLUS



2-piece impeller/magnet assembly

Large-dimensioned, metal-reinforced plain bearing engagement safely transmits the torque from magnet rotor to impeller. Exactly die-moulded geometries ensure a simple and durable assembly of magnet rotor and impeller by means of a jaw-type clutch design, fixed by a retaining ring, with easy dismantling.

No O-rings, no threads, no keyways needed.

2-piece design also for economical reasons: magnet coupling torque can be adjusted to changing demands by exchanging the magnet rotor and reusing the impeller. Even the impeller can be replaced individually.




Impeller magnet assembly (shown detached)

Solids restriction rings

Richter lined pumps can handle solids-laden fluids even with a higher percentage of contents. The allowable percentage of solids very much depends on the particle size, shape and hardness. Here Richter has long experience and recommends a case-by-case review by Richter engineering.

The solids restriction rings act as barrier to larger solid contents in the fluid to prevent them entering the can chamber. The inner solids restriction ring is integrally moulded into the magnet rotor as a standard feature. The outer solids restriction ring is made of PTFE and replaceable.



Parts and materials




Fig. : Frame-mounted pump RMI with grease lubrication




Fig. : Frame-mounted pump RMA with oil bath lubrication





Fig. : Close-coupled pump RMI-B

Fig. : Close-coupled pump RMA-B


Parts and materials

Item.	Designation	Material
100	Housing	Ductile iron EN-JS 1049/ASTM A395, PFA lining
122	Blind cover	Steel
158	Can insert	PTFE
159	Can	Carbon-fibre-reinforced fluoropolymer
213	Drive shaft	Steel
216	Hollow drive shaft	Steel
222	Shaft	SSiC pure silicon carbide, optionally with SAFEGSLIDE® PLUS
230	Impeller	PFA (core ductile iron 0.7040)
319	Impeller bearings	For materials, see relevant item
321/x	Radial ball bearing	Long-life grease, oil bath lubrication optional
330	Bearing pedestal	Ductile iron EN-JS 1049/ASTM A395
338	Shaft spider	SSiC pure silicon carbide
344	Lantern	Ductile iron EN-JS 1049/ASTM A395
346	Adapter	Ductile iron EN-JS 1049/ASTM A395
361	Rear bearing cover	Steel
401	Housing gasket	PTFE
404	Bearing pedestal gasket	PTFE
415/1	Centering gasket	PTFE
421/x	Radial shaft seal	
502	Outer solids restriction ring	PTFE, optional
504/x	Distance ring	PTFE
510/2	Front thrust ring	SSiC pure silicon carbide, optionally with SAFEGSLIDE® PLUS
510/3	Rear thrust ring	SSiC pure silicon carbide
523/1	Shaft sleeve	PTFE
545/x	Bearing sleeve	SSiC pure silicon carbide, optionally with SAFEGSLIDE® PLUS
566/x	Anti-torsion insert	PTFE
638/1	Constant level oiler	(only with oil bath lubrication)
672/1	Venting/filling plug	Polymer (only with oil bath lubrication)
858	Drive magnet assembly	Ductile iron, NdFeB permanent magnets
859	Inner magnet assembly	Steel/PFA, SmCo permanent magnets
903/1	Screw plug	Stainless steel (1.4301)
932/7	Circlip	PTFE


Additional options



Housing drain connection



Can leak sensor in lantern chamber



Temperature monitoring

Performance curves RMI, RMI-B (ISO/DIN)

Richter magnetic drive pumps
RMI and RMI-B are available for performance ranges of up to



- 130 m³/h (570 USgpm) and 70 m (230 ft) LC at 2900 rpm
- 150 m³/h (660 USgpm) and 100 m (330 ft) LC at 3500 rpm

The good hydraulics, the can system free of eddy currents, the almost maintenance-free design and the overall good value for money make the RMI/RMI-B series be one of the most economic pumps of its kind.

9 well graduated pump sizes from

40-25-125 to 80-50-200 allow for a tailor-made pump selection.


Flow rates and delivery heads outside this performance range can be covered by the **Richter magnetic drive pump series MNK/MNKA** up to 600 m³/h (2650 USgpm).



Dimensions and weights

for frame-mounted and close-coupled pumps with IEC and NEMA motors

Frame-mounted pump RMI




Pump dimensions in mm (inch)

Gr.	Pump size	DN _S	DN _D	a	B	d ₂	f	h ₁	h ₂	L	I	GA	F	LP	Weight kg (lbs)			
1.1	40-25-125	40 (1.57)	25 (0.98)	80	240	24	385	112	140	465	50	27	8	36	41			
	50-32-125	50 (1.97)	32 (1.26)	(3.15)	(9.45)	(0.94)	(15.16)	(4.41)	(5.51)	(18.31)	(1.97)	(1.06)	(0.31)	(1.42)	42			
1.2	40-25-160	40 (1.57)	25 (0.98)	80	280	24	385	132	160	465	50	27	8	36	57			
	50-32-160	50 (1.97)	32 (1.26)	(3.15)				(5.2)	(6.3)						(18.31)	58		
	80-50-160	80 (3.15)	50 (1.97)	100 (3.94)				160 (6.3)	180 (7.09)	485 (19.09)					65			
	80-65-160	80 (3.15)	65 (2.56)												68			
1.3	50-32-200	50 (1.97)	32 (1.26)	80 (3.15)	330	24	385	160	180	465 (18.31)	50	27	8	36	91			
	65-40-200	65 (2.56)	40 (1.57)	(13)					(0.94)	(15.16)					(6.3)	(7.09)	485	93
	80-50-200	80 (3.15)	50 (1.97)	(3.94)												200 (7.87)	(18.1)	95

Pump feet dimensions in mm (inch)

Gr.	Pump size	b	m ₁	m ₂	m ₃	m ₄	n ₁	n ₂	n ₃	n ₄	S ₁	S ₂	w
1.1	40-25-125	50 (1.97)	94 (3.7)	50 (1.97)	50 (1.97)	19 (0.75)	190 (7.5)	140 (5.51)	110 (4.33)	145 (5.71)	14 (0.55)	14.5 (0.57)	285 (11.2)
	50-32-125										14.5 (0.57)		
1.2	40-25-160	50 (1.97)	100 (3.94)	70 (2.76)	50 (1.97)	19 (0.75)	240 (9.45)	190 (7.5)	110 (4.33)	145 (5.71)	14.5 (0.57)	14.5 (0.57)	285 (11.2)
	50-32-160												
	80-50-160												
	80-65-160						265 (10.43)	212 (8.35)					
1.3	50-32-200	50 (1.97)	100 (3.94)	70 (2.76)	50 (1.97)	19 (0.75)	240 (9.45)	190 (7.5)	110 (4.33)	145 (5.71)	14.5 (0.57)	14.5 (0.57)	285 (11.2)
	65-40-200												
	80-50-200						265 (10.43)	212 (8.35)					

Close-coupled pump RMI-B



Pump dimensions in mm (inch)

Gr.	Pump size	DN _S	DN _D	a	B	N ₁	h ₁	h ₂	Weight kg (lbs)
1.1	40-25-125	40 (1.57)	25 (0.98)	80	240	161	112	140	28
	50-32-125	50 (1.97)	32 (1.26)	(3.15)	(9.45)	(6.34)	(4.41)	(5.51)	29
1.2	40-25-160	40 (1.57)	25 (0.98)	80	280 (11.02)	153 (6.02)	132 (5.2)	160 (6.3)	40
	50-32-160	50 (1.97)	32 (1.26)	(3.15)					41
	80-50-160	80 (3.15)	50 (1.97)	100 (3.94)			160 (6.3)	180 (7.09)	48
	80-65-160		65 (2.56)						51
1.3	50-32-200	50 (1.97)	32 (1.26)	80 (3.15)	330 (13)	170 (6.69)	160 (6.3)	180 (7.09)	64
	65-40-200	65 (2.56)	40 (1.57)	100 (3.94)					66
	80-50-200	80 (3.15)	50 (1.97)					200 (7.78)	68

Pump feet dimensions in mm (inch)

Gr.	Pump size	b	m ₁	m ₂	n ₁	n ₂	S ₁
1.1	40-25-125	50	94	50	190	140	14 (0.55)
	50-32-125	(1.97)	(3.7)	(1.97)	(7.5)	(5.51)	14.5 (0.57)
1.2	40-25-160	50 (1.97)	100 (3.94)	70 (2.76)	240 (9.45)	190 (7.5)	14.5 (0.57)
	50-32-160						
	80-50-160				265 (10.43)	212 (8.35)	
	80-65-160						
1.3	50-32-200	50 (1.97)	100 (3.94)	70 (2.76)	240 (9.45)	190 (7.5)	14.5 (0.57)
	65-40-200						
	80-50-200					265 (10.43)	

Adapter dimensions (IEC motors) in mm (inch)*

Gr.	IEC-Motor	N ₂	P	N	M	S	m ₃	m ₄	n ₃	n ₄	S ₂	w	h ₅	
1.1	80 B	107 (4.21)	200 (7.87)	130 (5.12)	165 (6.5)	11.5 (0.45)	50 (1.97)	19 (0.75)	110 (4.33)	145 (5.71)	14.5 (0.57)	219 (8.6)	112 (4.41)	
	90 S													
	90 L													
	100 L	148 (5.83)	250 (9.84)	180 (7.09)	215 (8.46)	14 (0.55)						255 (10.04)	132 (5.2)	
	112 M													
	132 S													
	132 M	137 (5.39)	300 (11.81)	230 (9.06)	265 (10.43)							244 (9.61)	160 (6.3)	
1.2	80 B	115 (4.53)	200 (7.87)	130 (5.12)	165 (6.5)	11.5 (0.45)	43 (1.69)	14 (0.55)	0	100 (3.94)	16 (0.63)	184 (7.24)	132 (5.2)	
	90 S													
	90 L									60 (2.36)				
	100 L	156 (6.14)	250 (9.84)	180 (7.09)	215 (8.46)	14 (0.55)	50 (1.97)	19 (0.75)	110 (4.33)		145 (5.71)	14.5 (0.57)	244 (9.61)	160 (6.3)
	112 M													
	132 S													
	132 M	145 (5.71)	300 (11.81)	230 (9.06)	265 (10.43)									
	160 M	175 (6.89)	350 (13.78)	250 (9.84)	300 (11.81)	18 (0.71)	from motor size 160 no support bracket							
	160 L													
180 M														
1.3	100 L	184.5 (7.26)	250 (9.84)	180 (7.09)	215 (8.46)	14 (0.55)	50 (1.97)	19 (0.75)	110 (4.33)	145 (5.71)	14.5 (0.57)	300.5 (11.8)	160 (6.3)	
	112 M													
	132 S													
	132 M													
	160 M	199 (7.83)	350 (13.78)	250 (9.84)	300 (11.81)	18 (0.71)	from motor size 160 no support bracket							
	160 L													
	180 M													
	200 L													
	225 S													
225 M	400 (15.75)	300 (11.81)	350 (13.78)											



* see page 9 for adapter dimensions in mm (inch) for NEMA motors

Performance curves RMA, RMA-B (ASME/ANSI)

Richter magnetic drive pumps
RMA and RMA-B are available for
performance ranges of up to

- 250 m³/h (1100 USgpm) and
110 m (360 ft) LC at 2900 rpm
- 300 m³/h (1320 USgpm) and
155 m (500 ft) LC at 3500 rpm

9 well graduated sizes from
1.5x1x6" to 6x4x10" allow for a
tailor-made pump selection.




* 6x4x10" for speeds up to 1450 and 1750 rpm

Dimensions and weights

for frame-mounted and close-coupled pumps with IEC and NEMA motors

Frame-mounted pump RMA




Pump dimensions in mm (inch)

Gr.	Pump size	DN _s	DN _b	Y	T	U	N	O	D	X	CP	V	R	S	ES	Weight kg (lbs)	ASME B73.3
1	1.5x1x6"	38.1 (1.5)	25.4 (1)	102 (4.02)	280 (11.02)	22.3 (0.87)	343 (13.5)	298 (11.75)	133 (5.25)	165 (6.5)	445 (17.52)	51 (2)	24.3 (0.96)	4.8 (0.19)	44.5 (1.75)	56	AA
	3x1.5x6"	76.2 (3)	38.1 (1.5)													58	AB
	3x2x6"	76.2 (3)	50.8 (2)													61	AC
	1.5x1x8"	38.1 (1.5)	25.4 (1)		290 (11.4)											58	AA
2	3x1.5x8"	76.2 (3)	38.1 (1.5)	102 (4.02)	330 (13)	28.6 (1.13)	495 (19.5)	425 (16.7)	210 (8.25)	216 (8.5)	597 (23.5)	82 (3.23)	31.4 (1.24)	6.35 (0.25)	57.2 (2.25)	95	A50
	3x2x8"	76.2 (3)	50.8 (2)					450 (17.75)		242 (9.5)						100	A60
	4x3x8"	101.6 (4)	76.2 (3)					490 (19.3)		280 (11.02)						106	A70
	3x2x10"	76.2 (3)	50.8 (2)		380 (15)			450 (17.75)		242 (9.5)						113	A60
	6x4x10"	152.4 (6)	101.6 (4)		424.8 (16.72)			597 (23.5)	254 (10)	343 (13.5)		80 (3.15)				135	A80

Pump feet dimensions in mm (inch)

Gr.	Pump size	B	M ₁	A ₁	M ₂	A ₂	K ₁	E ₁	E ₂	K ₂	H ₁	H ₂	F
1	1.5x1x6"	50 (1.97)	78 (3.07)	36 (1.42)	43 (1.69)	14 (0.55)	202.4 (7.97)	152.4 (6)	0	100 (3.94)	16 (0.63)	16 (0.63)	184 (7.25)
	3x1.5x6"		83 (3.27)	41 (1.61)									
	3x2x6"		83 (3.27)	41 (1.61)									
	1.5x1x8"		78 (3.07)	36 (1.42)									
2	3x1.5x8"	50 (1.97)	83 (3.27)	41 (1.61)	54 (2.13)	25 (0.98)	298 (11.7)	248 (9.76)	184 (7.25)	220 (8.66)	16 (0.63)	16 (0.63)	318 (12.5)
	3x2x8"		90 (3.54)	45 (1.77)									
	4x3x8"		83 (3.27)	41 (1.61)									
	3x2x10"	80 (3.15)	110 (4.33)	60 (2.36)	54 (2.13)	25 (0.98)	328 (12.91)	248 (9.76)	184 (7.25)	220 (8.66)	16 (0.63)	16 (0.63)	318 (12.5)
	6x4x10"												

Close-coupled pump RMA-B



Pump dimensions in mm (inch)

Gr.	Pump size	DN _S	DN _D	D	N ₁	O	T	X	Y	Weig. kg
1	1.5x1x6"	38.1 (1.5)	25.4 (1)	133 (5.25)	152.9 (6.02)	298 (11.75)	280 (11.02)	165 (6.5)	102 (4.02)	41
	3x1.5x6"	38.1 (1.5)	38.1 (1.5)							43
	3x2x6"	76.2 (3)	50.8 (2)							46
	1.5x1x8"	38.1 (1.5)	25.4 (1)				290 (11.4)			44
	3x1.5x8"	76.2 (3)	50.8 (2)				425 (16.7)			65
2	3x2x8"	101.6 (4)	76.2 (3)	210 (8.25)	169.9 (6.69)	490 (19.3)	330 (13)	280 (11.02)	102 (4.02)	70
	4x3x8"	76.2 (3)	50.8 (2)				450 (17.75)			76
	3x2x10"	152.4 (6)	101.6 (4)				450 (17.75)			83
	6x4x10"	152.4 (6)	101.6 (4)				597 (23.5)			105
	3x1.5x8"	76.2 (3)	50.8 (2)				425 (16.7)			65
	3x2x8"	101.6 (4)	76.2 (3)				450 (17.75)			70

Adapter dimensions (NEMA motors) in mm (inch)*

Gr.	NEMA Motor	N ₂	BD	AK	AJ	BF
1	140 TC	114.9 (4.52)	170 (6.7)	114.3 (4.5)	149.23 (5.88)	11.1 (7/16)
	180 TC	145 (5.71)	235 (9.25)	215.9 (8.5)	184.2 (7.25)	14.3 (9/16)
	210 TC	161 (6.34)	255 (10)	266.7 (10.5)	228.6 (9)	
	250 TC	145 (5.71)	285 (11.22)	317.5 (12.5)	279.4 (11)	
	280 TSC	155 (6.1)	355 (14)	317.5 (12.5)	279.4 (11)	
	320 TSC	190.5 (7.5)	355 (14)	317.5 (12.5)	279.4 (11)	17.5 (11/16)
2	180 TC	184.5 (7.26)	235 (9.25)	215.9 (8.5)	184.2 (7.25)	14.3 (9/16)
	210 TC					
	250 TC					
	280 TSC					
	320 TSC	190.5 (7.5)	355 (14)	317.5 (12.5)	279.4 (11)	17.5 (11/16)
	400 TSC					

*see page 7 for adapter dimensions in mm (inch) for IEC motors

Pump feet dimensions in mm (inch)

Gr.	Pump size	B	M ₁	A ₁	M ₂	A ₂	K ₁	E ₁	E ₂	K ₂	H ₁	H ₂	F
1	1.5x1x6"	50 (1.97)	78 (3.07)	36 (1.42)	43 (1.69)	14 (0.55)	202.4 (7.97)	152.4 (6)	0	100 (3.94)	16 (0.63)	16 (0.63)	184 (7.24)
	3x1.5x6"		83 (3.27)	41 (1.61)									
	3x2x6"		83 (3.27)	41 (1.61)									
	1.5x1x8"		78 (3.07)	36 (1.42)									
2	3x1.5x8"	50 (1.97)	83 (3.27)	41 (1.61)	56 (2.2)	25 (0.98)	298 (11.7)	248 (9.76)	184 (7.24)	220 (8.66)	16 (0.63)	16 (0.63)	318 (12.5)
	3x2x8"		90 (3.54)	45 (1.77)									
	4x3x8"		83 (3.27)	41 (1.61)									
	3x2x10"	80 (3.15)	110 (4.33)	60 (2.36)	54 (2.13)	25 (0.98)	328 (12.91)	248 (9.76)	184 (7.24)	220 (8.66)	16 (0.63)	16 (0.63)	318 (12.5)
	6x4x10"												

Other Richter process pumps

Richter magnetic drive and mechanical seal pumps are used – just like Richter chemical shut-off, control and safety valves – in different chemical and related processes. This pump range also includes more specialised designs. The plant operator can thus choose from Richter pumps even for very difficult applications.

Mechanical seal pumps

- to DIN/EN 22858/ISO 2858 up to 300 m³/h (1320 USgpm) and 90 m (300 ft) LC
- to ASME B73.1 up to 115 m³/h (300 ft) and 105 m (350 ft) LC

Self-priming pumps

for emptying containers and basins from the top. Suction height up to 6 m (20 ft) WC, suction back pressure up to 18 m (59 ft) LC. Up to 33 m³/h (145 US gpm) and 40 m (130 ft) LC at 2900 and 55 m (180 ft) at 3500 rpm.

Magnetic drive pumps

- to DIN/EN 22858/ISO 2858 up to 600 m³/h (2650 USgpm) and 90 m (300 ft) LC
- to ASME B73.3 up to 300 m³/h (750 USgpm) and 155 m (500 ft) LC

Vortex pumps

for media with solid contents and lumpy particles and media with higher gas contents. Up to 200 m³/h (880 USgpm) and 85 m (280 ft) LC at 2900 rpm and 120 m (395 ft) at 3500 rpm.

Peripheral pumps

for lower flow rates at high heads. Up to 0.1-5 m³/h (0.4-22 USgpm) and up to 100 m (330 ft) LC



**Valve
& Automation**
Total Valve & Control Solutions®

JOHANNESBURG
Tel: 011 397 2833

DURBAN
Tel: 031 579 2593

South Africa:
0861 103 103

E-mail: sales@valve.co.za
www.valve.co.za



SCAN ME